

1) Publication number:

0 564 077 A2

© EUROPEAN PATENT APPLICATION

- (1) Application number: 93300874.0
- (F) Int. Cl.5: A23G 1/00

- ② Date of filing: 05.02.93
- @ Priority: 20.02.92 US 839525
- ② Date of publication of application: 06.10.93 Bulletin 93/40
- Designated Contracting States: AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE
- Applicant: KRAFT GENERAL FOODS, INC. 250 North Street
 White Plains New York 10625(US)
- @ Inventor: Fitch, Mark David 7 Maple Avenue Stonybrook, New York 11780(US) Inventor: Anderson, Wendy Ann 347 West End Avenue No.24 New York, New York 10024(US) Inventor: Eckhardt, Gerard 413 Linden Street Bellmore, New York 11710(US) Inventor: Anelich, Mario Anthony 63 Merritt Avenue Dumont, New Jersey 07628(US) Inventor: Frake, Barry Neil 1 Gull Cove Northport, New York(US) Inventor: Lang, Kevin Walter 1 Tulip Drive
- Representative: Eyles, Christopher Thomas W.P. THOMPSON & CO. High Holborn House 52-54 High Holborn London WCTV 6RY (GB)

Lloyd Neck, New York 11743(US)

- Section Low-fat confectionary material and process for making same.
- Fat in a confectionary chip is reduced to below about 10% by using a low-fat insoluble, non-gummy food material and small particle sugar (less than 100 microns) in combination with about 13% moisture. The sugar to non-gummy food material ratio must be between 2·1 and 4·1 and the moisture between about 10% to about 15%. Hydrated food ingredients are added to retain at least some of the moisture in the bound state. Other ingredients which may be added to the formulation include syrups, milk solids and starch. The chips can be made by simply blending the dry ingredients and adding the moisture to form a dough in the form of adv, crumbly paste. The dough is mixed or worked up well and then formed into the desired shape. The shape is then cut into pieces similar to chocolate chips.

TECHNICAL FIELD

The present invention relates to a low-fat confectionary material, such as a chip or bit and, more particularly, to a themostable low-fat confectionary chip suitable for use in flat-free products such as backed so goods, cookies, confections, instant puddings and loe cream. Low-fat confectionary material, as defined in this invention, means below 1/3 the level of fat normally found in the traditional material. For example, in the case of a chocolate chip, the cocoa butter present in the chocolaty chip of this invention is below 10%, preferably below 1%. Fat-free products, as defined in this invention, means less than 1/2 gram of fat per serving. These products can include chocolate chips having up to 10% cocoa butter in the chip. The products can include chocolate chips having up to 10% cocoa butter in the chip. The products in the chip of the confectionary chips and incorporating these chips into fat-free food products.

DESCRIPTION OF THE PRIOR ART

Many prior art disclosures recite the incorporation of water-binding materials, such as gums and cellulosic fiber, into food products to reduce the fat content of these products. These teachings, however, have not enabled the production of high-quality, low-fat confectionary chips, such as chocolate chips, which have been widely accepted in the marketplace. Among such prior at patents are: U.S. Patents 3.23-0,027 to Jartson et al.; 3.57-6,934 to Singer, 4.109,018 to Thompson; 4.143,163 to Hutchinson et al.; 4.198,043 to Singer et al.; 4.198,043 to Gildesman et al.; 4.197,040 to Feeney et al.; 4.24,9468 to Hotgoen et al.; and published EPO application 340,035 and published EPO application 40,035 and 4

There are no low-fat chips which have good textural, flavor and function characteristics. The function attributes necessary for chips in baked goods include the thermal stability to retain distinct shape throughout the heat of baking, and the mechanical stability to remain intact during the dough or batter brings gatage of a product. Making a low-fat chip requires a unique approach to formulation and processing. In the case of a chocolate chip, the cocoa butter is 36% of the formula (by weight), and it functions as an ingredient binder, a structural agent, a flavor carrier, and a textural or mouthfeel agent. The main requirements for confectionary fats are a reasonably hard consistency, stability, and a short melting range just below body temperature. Cocoa butter is the primary fat source found in chocolate, and is defined as the edible fat obtained from cocoa beans. Cocoa butter exhibits a sharp melting point at 98°F (6.87°C), 36° with a softening of the cocoa butter around 90°F (62.2°C). This melt profile of the cocoa butter provides the primary functional role of fat in chocolate, the "melt-in-the-mount" textural properties. Cocoa butter also contracts uono solidification which allows molding and shadning of chocolate without sticking to the molds.

The cocca butter in a traditional chocolate chip serves several functions. First, it provides the sensory benefits to d a creamy mouthed due to the fact that cocca butter melts sharply at 98 F (8.67.°C), at or 49 below body temperature. The fat also carries flavor and allows this flavor to dwell on the taste buds, thereby enhancing the chocolate sensation. In addition to the sensory benefits of fat in chocolate, the fat serves several functional roles in the chocolate piece. The fat binds the cocca and sugar together to form a paste. It provides the structure of the piece, and it lubricates and contracts to self-extract from molds. Lastly, the cocca butter, in combination with sugar, provides a fragile but definite structure to the chip during baking so 45 that the chip retains it's shape in the oven. In order to simulate chocolate without using fats, all of the above mentioned benefits must be addressed. However, it should be noted that the legal requirements or standards of identity for chocolate require that the chocolate contain more than 30% cocca butter to be called "chocolate". Thus, a fat-free chocolate-flavored material with little or no added cocca butter cannot be labelled or called "chocolate" even though it tastes like chocolate. The low-fat material of this invention so will be referred to as a "chocolaty writerial" and will bioscience.

It would be desirable if a fat replacer for the fat, such as cocoa butter, in a confectionary material, such as chocolate, could be produced having the properties of that fat as to mouthfeel, taste, structure and "binding" properties.

It would also be desirable to produce a low-fat confectionary material having good textural, flavor and functional characteristics.

It would still further be desirable if the low-fat confectionary material had the thermal stability to retain its distinct shape throughout the heat of baking and the mechanical stability to remain intact during the dough or batter mixing stage for making the food product.

SUMMARY OF THE INVENTION

This invention is founded on the discovery that the fat in a confloctionary material can be reduced to below about 10%, preferably below about 1%, by mixing granulated sugar and granulated or powdered s insoluble, non-gummy food material together at a moisture content of about 10% to about 15%, said sugar comprising a particle size of below 150 microns (preferably below 80 microns) and said sugar to insoluble, non-gummy food material ratio on a weight basis being between about 21 and about 41.

The insoluble, non-gummy food material can be any existing food ingredient which is insoluble in water and somewhat stable to normal processing conditions. This includes ground cocoe beans, varilla, roasted roffee, nuts (peanut, walnut, hazelnut, pecan, cashew, etc.), coconut, cellulose, cerael fiber (oat, wheat, barley rice, corn, etc.), vegetable fiber, insoluble proteins (lactalbumin, egg albumin, zein, legume meal, sunflower seed, cotton seed, etc.), edible mineral salts, citric waste and bone meal, this preferred that this insoluble, non-gummy material be low in fat content, typically less than 15% fat.

Preferably, a hydrated food ingredient, such as gum, insoluble fiber, and/or protein may be used as a 15 moisture source to provide most or essentially all of the requisite moisture content. These hydrated food ingredients will supply both a source of free moisture and a source of bound or retained moisture. Syrup, milk solids and starch can also be added to the formulations.

The confectionary chip or bit can be made by simply blending the dry ingredients and adding the moisture to form a dough in the form of a dry, crumbly paste. The dough is mixed or worked up well and at then formed into a desired shape. The shape is then cut into pieces such as chips or bits.

All ratios, parts, and percentages (%) recited in this Specification and Claims are by weight.

DETAILED DESCRIPTION OF THE INVENTION

This new confection formula resembles a fudge or fondant candy. The traditional methods for making these candy products involves a hot process which adds excess moisture to dissolve the sugar, boils off moisture to supersaturate the solution, and then agitates to form small, uniform sugar crystals which are smooth in mouthleel and provide shape to the end product. The resulting mix is very sticky and hard to shape and cut during processing. The processing portion of this invention eliminates the addition of excess we water to the formula. Using a small particle sugar (preferably less than 60 microns) for smoothness, and adding no more than about 15% total moisture, the process is simplified this cold process, requires mixing the ingredients and forcing them through a die supplied with a rotary knife to cut off small lengths, then tumbling the cut pleces to round off and emooth the surfaces. In this cold process, the flavor profile is improved due to the elimination of heat degradation of the flavor systems. Important parameters include: so control of added moisture, control of the amount of work added to the dough, and control of the ratios of sugar to the providered insoluble, non-gummy food materials, such as occoal in the case of a chocalate chip. These chips are relatively easy to make and perform very well in baked products. The chips resist crumbling in the mixer, and retain their shape during baking.

Chocolate chips are normally made from chocolate. Standard chocolate recipes call for sugar, cocoa, occae butter, milk solids, lecithin, an emulalifier, vanillin and flavors. According to this invention, this standard recipe can be altered by reducing the fat (cocoa butter) and replacing it with small particle size sugar and low-tat cocoa (under 15% fat) at a ratio of between about 2:1 and about 4:1 in combination with a total moisture level about 10-15% to thereby make a low-tat chip. The moisture is usually added in the form of the control of the contro

The low-fat cocca, small particle sugar and selected hydrated food ingredients in the aqueous dispersion serve not only as the fat replacement but also as the primary flavor carrier and ingredient binder for this chip. Thus, the cocca butter, and emulsifiers can be eliminated and an excellent low-fat chocally chip can be made. The small particle sugar is typically sucrose, but other crystalline sugars can be used. The sucrose or other small granular sugar must be in powdered or crystalline form and have a small particle size of below about 150 microns, preferably below 100 microns, and most preferably under 60 microns, say 30 to 50 microns in particle size. The small particle size contributes to the desired "melt-in-the-mouth" sensation that traditional chocolate chips exhibit.

In the case of a nut chip, the cocca powder is simply replaced with a low-fat nut flour, such as peanut four having less than 15% fat, but the same ratios apply. If a full fat peanut flour is used, it may be mixed with a vegetable fiber or cereal fiber to lower the fat content of the insoluble, non-gummy food material to under 15% fat. In the case of a "white" or neutral chip, only a vegetable fiber may be used, but the level of milk solids may have to be increased.

The preferred hydrated food ingredients in the aqueous dispersion are hydrated polysaccharide hydrocolloids in combination with hydrated insoluble fibers, and protein materials. These hydrated food ingredients help to give the low-fat chip of this invention texture, mouthfeel, softness, and fatty mouthfeel similar to traditional chocolate. They also prevent moisture migration and impart lubricity to the product.

It is possible to use hydrated polysaccharide hydrocolloids, hydrated insoluble fiber, or hydrated protein dispersions alone or in any combination thereof while still producing an acceptable confectionary chip. In fact, any solid food material which is hydrated and capable of releasing its moisture to the surrounding chip ingredients can be used.

The hydrated, polysaccharide hydrocolloids, insoluble fiber and/or protein material apparently are able 15 to function as a reservoir of bound moisture capable of slowly releasing this moisture from the chip into a cookie or other baked product. It is also speculated that, in any fiber-polysaccharide hydrocolloid combination, the fiber component disrupts or reduces any gummy texture which could result from the presence of the polysaccharide hydrocolloids. The polysaccharide hydrocolloids, insoluble fiber and/or protein are incorporated into the chip in a hydrated state, typically in a single, preformed aqueous dispersion. However, 20 it is possible to utilize separate aqueous dispersions for each of the materials to be hydrated. Each of these hydrated materials can be used alone, as the partial or total moisture source. The addition of unhydrated polysaccharide hydrocolloids, insoluble fiber and/or protein directly to chip ingredients together with a separate portion of water is discouraged since this does not usually provide enough water and/or time to permit adequate hydration. Materials such as cocoa and sugar absorb large amounts of water before the polysaccharide hydrocolloids, insoluble fiber and/or protein materials are hydrated. The added aqueous dispersion preferably should have a thick, paste-like consistency and a viscosity of at least 6, preferably at least 12, as measured at 40 °F (4.4°C) using a Brookfield Model HAT Viscometer with a helipath stand and a size-D, T-Bar spindle at 5 RPMs (scale 0-100). The aqueous dispersion should also have a solids content. basis the amount of polysaccharide hydrocolloid, insoluble fiber, protein and water components present in 30 the dispersion, of from 2 to 35% by weight, preferably from 5 to 30% and most preferably from 9 to 25%.

The polysaccharide hydrocolloids used in this invention as a partial or total moisture source are preferably water-soluble, non-gelling gums, such as xanthan, guar, methylocolluses, actoxymethyl cellulose and the like. Gums which form gels, such as alignates, pactin, kappa and tota carrageenan and the like while not preferred can also be used. Non-polysaccharide hydrocolloids us but as gelatin, can also be used. So preferred. The anionic polysaccharide hydrocolloid and a galactomannan polysaccharide hydrocolloid is preferred. The anionic polysaccharide should include within its molecular structure dependent carboxylic acid groups. Xanthan gum and carboxymethyl cellulose are such polysaccharides. Galactomannan are polysaccharide composed solely of mannose and galactose. Guar gum, a galactomannan which has a mannose-polysalcose ratio of about 13.1 has proven to be well-suited for this use. Combinations of xanthan up um and guar at a weight ratio of 1.4 to 4.1, preferably about 1:1, have been found to be highly suitable. Xanthan gum is a high molecular weight polysaccharide which is cotalend by pure culture fermentation of glucose with a bacterium of the genus Xanthamonas, such as Xanthomonas campestris. Xanthan is a heteropolysaccharide made up of bullding blocks of Dejucose, D-mannose and D-glucorion acid. Guar in the seeds of the guar bean (Cyamposis Tetragonaolobas L. taub.) which is native to

The insoluble fiber which may be employed in this invention as a partial or total moisture source can be any edible fiber material, including powdered cellulose (at least 95% insoluble fiber). Fiber derived from cereal grains (e.g., oat, wheat, com, soy, etc.) is well-suited for use in this invention. Oat fiber, which contains a relatively-high level (at least 85%) of insoluble fiber, soy fiber and wheat fiber have been successfully used in the practice of this invention.

The protein material which can be used in this invention as a partial or total moisture source may be an essentially-pure protein, as in the case of whey protein or casein, or as part of a protein containing material, such as dry non-fat milk solids, dried egg whites, soy protein, wheat protein, wheat gluten, etc. Non-fat milk solids (about 38% protein) and wheat gluten have been found to be useful. Proteins, such as casein, which so form protein micelles in an aqueous dispersion should also be suitable. The protein may be at teast partially denatured as denatured protein has higher water absorption properties than undenatured protein.

According to this invention, the dispersions may be used in place of fat. Preferably the dispersions are prepared so that the use of the dispersion for fat will be at a ratio of 0.5-1.5:1, typically about 1:1. Baked

goods such as chocolaty chip cookies which have a fat content of less than 0.5 grams per serving are considered to be included in the term "fat-free".

The polysaccharide hydrocolloids should be included in chip formulations at a level of from 0.1 to 4.0, preferably 0.25 to 2.0, parts per 100 parts of solid sugar used in the formulation. The insoluble liber should be used at a level of 0.1 to 5.0, preferably 0.1 to 2.0 per 100 parts of solid sugar. Protein should be included in the chip formulation at a level of at least 0.1 to 8.0, preferably 0.5 to 3 parts per 100 parts of solid sugar. If will be destrable that the ratio of hydrocolloid to protein in the dispersion be from 1:1-4.5.

A benefit derived from the use of a prepared aqueous dispersion is that any of the materials contained therein can be hydrated at a location or time remote from the production of the chip. According to a specific embodiment of this invention, aqueous dispersions are prepared which contain polysaccharide hydrocolloid, insoluble fiber and protein at a weight ratio of 1:0.86-0:1.1-4.5, preferably 1:1.5-2.02.0-3.0. The aqueous dispersion may be prepared by any technique which both hydrates the ingredients and produces a uniform distribution of solids within a stable aqueous dispersion. Typically, a procedure is followed in which the dry ingredients are first combined in a batch-type mixer and the resulting mix is passed through a mixing units which will produce a uniform aqueous dispersion, such as a homogenizer or a continuous mixer. Thereafter, the dispersion should be pasteurized such as by heating to advoce about 160 °F (about 71.1 °C) for up to 10 minutes. The dispersion is preferably maintained at about 40 °F (4-2 °C) or below in order to ensure microbial stability. Cooling of the dispersion below 45 °F (7.2 °C) prior to use in the chocolary chip is thought to be desirable even in the event the dispersion is utilized immediately after productly after productly after productly and the contraction.

A generic version of the formulation for the confectionary chip of this invention is as follows:

30

Ingredients	Range % by Weight	Preferred % by Weight
Sugar (solid)	40-70	55-65
Low-fat Insoluble, Non-Gummy Food	12-35	15-25
Moisture Source	6-18	9-15
Syrup	2-6	3-5
Non-Fat Milk Solids	2-6	3-5
Flavor/Salt	0.1-2.0	0.1-2.0

The solid sugar is preferably sucrose, but other crystalline sugars, such as dextrose, glucose, lactose. 35 fructose, maltose, etc. can be used. Also, other liquid sugars can be added to the solid sugar as long as the solid sugar to liquid sugar ratio is kept above 5:1. Most preferably, at least 80% of the total sugar is crystalline sucrose. The solid sugars should have a small particle size of less than 150 microns, preferably less than 100 microns and most preferably less than 60 microns. Confectionary sugar (10X) has a suitable particle size of about 50 microns for the chip formulation. However, the smaller the particle size of the 40 sugar, the better the mouthfeel. The low-fat insoluble, non-gummy food material can be ground cocoa, vanilla, roasted coffee, nuts (peanut, walnut, hazelnut, pecan, cashew, etc.), coconut, cellulose, cereal fiber (oat, wheat, barley rice, corn, etc.), vegetable fiber, insoluble proteins (lactalbumin, egg albumin, zein, legume meal, sunflower seed, cotton seed, etc.), edible mineral salts, citric waste and bone meal. In fact, any existing food material that is insoluble in water and stable against normal processing conditions can be 45 used. High fat containing food materials, such as cocoa powder and peanut flour are preferably defatted to a level of under 15% fat. Of course, lower fat levels of below about 2% and below about 1% are most preferred. In the case of a vegetable fiber or cereal fiber, no defatting is necessary since little or no fat exists. This latter material can be mixed with the high fat material (such as cocoa or peanut) to lower the fat content to below 15% fat. The moisture source, as stated, can be any edible food material capable of 50 delivering up to the required 10-15% moisture to the chip. However, it is preferable that most of the moisture be supplied in the form of one of the moisture sources enumerated above. The syrup can be any liquid sugar which does not crystallize out during processing, is highly hygroscopic, and provides softness to the confectionary chip. Suitable syrups that can be used in the formulation are invert sugar, glycerin, high fructose corn syrup and fructose syrup. The non-fat milk solids may be any dry, low fat milk solids. The 55 milk solids help to mellow the flavor of the chips and help to bring out desired flavor. The flavors may include natural, artificial or a combination of natural and artificial flavors. The salt is useful as an hygroscopic agent to help control water activity and enhance flavor in the chip. Crystalline fructose (particle size under 150 microns) can also be used as a hygroscopic agent to control the water activity in the

formulation.

The sensory benefits of a confectionary mouthfeel are addressed in two different manners. A fatty mouthfeel is simulated with about 10 to 15% moisture, in combination with small particle sugars (less than 150 microns and preferably under about 60 microns) which are not perceived as "grainy" in the mouth. The moisture and sugar provide a "melt-in-the-mouth" sensation as the sugar dissolves in the saliva.

In the case of chocolate chips, the flavor systems are addressed by addition of cocoa powder and chocolate flavor either artificial, natural or both. The flavor can be enhanced by the use of refined chocolate powder or occoa which has undergone dutching to develop a more intense chocolaty flavor. This chocolate powder and/or dutched cocoa can then be ground to between about 20 to 28 microns and blended with the remaindance compared to give a better chocolate flavor. Since the chocolate powder contains cocoa butter, care has to be taken to keep the level sufficiently low so as not to exceed the low-fat requirements.

As previously mentioned, in regular chocolate chips, the sugar and fat provides structure to the chip. However, since the chips of this invention have virtually no fat, other ingredients must combine with the sugar to provide the destred structure to the chip. The chip consists of sugar and occoa held together using a moisture source. The moisture source as well as the sugar crystals provide structure to the chocolate piece. The moisture source adds mechanical stability in the mixer as well as thermal stability in the oven. In order to achieve that stability, several factors must be controlled.

The ratio of crystalline sugar to the insoluble, non-gummy food material is critical in making the low-fat confectionary material of this invention. In the case of chocotaly chips, the optimal sugar to cocoa artio is between 2:1 and 4:1. If the sugar to cocoa level is greater than 4:1, the chip will melt very quickly in the oven. If the sugar to cocoa level is less than 2:1, the chip will have very high thermal stability, and will cumble in the mixer. This same ratio applies in making a nut high except that peanut flour (defatted to below 15% fat) is used in place of the cocoa. If a full fat peanut flour is used, it must be mixed with a vegetable fiber or a cereal fiber in order to lower the fat content to a suitable level.

25 This produces a suitable nut chip which can be flavored to provide a walnut, hazelnut, pecan or other nut flavor. In the case where a "white" chip is desired, this can be made by using only a vegetable fiber or a cereal fiber in place of the cocoa powder.

In addition to major ingredient ratios, the total moisture content is critical to chip stability, both mechanical and thermal. As the total moisture content rises above about 15%, the chip paste becomes very sticky and difficult to process, the thermal stability during baking decreases, and melting occurs. As the moisture level drops below about 10%, the mechanical stability of the chip decreases and it becomes difficult to from the chip into pieces.

Furthermore, if the moisture is not given an opportunity to redistribute itself after chip formation, the chip will melt during the bake. This can be demonstrated in chips that are founds frozen' and in chips that are used immediately after formation. The moisture in these "young" chips is not given the time to equilibrate within the chip system and the chips melt during baking. When the chip is "aged", the moisture associates with ingredients in the chip, resulting in a chip that is less likely to melt during baking. This "aging" or "tempering" of the chip can be accomplished in several hours, say 6 to 12 hours, but 24 hours is preferred.

Another way to achieve the "aging" effect is though increased energy added to the chip during the mixing state. This added energy results in a chip with lower moisture (later baking) than the same chip mixed at a lower energy level. The relative energy ratio can be determined by computing the rotational velocity of the mixer on different speed settings. The RPMs at each setting is counted by ying a string around the padded and running the mixer for a set time. The RPMs are determined directly by counting the set number of coils per unit time. The energy ratio is equal to the RPMs sugared. Baking studies of chips mixed at an energy ratio above 400:1 based on the rotational speed squared, indicate that the high energy chips have a lower total moisture content postbale, with a larger percentage of this moisture as freezable water. This lower moisture content in the baked chip indicates that the chips mixed at high energy lose more moisture during the baking process than the low energy chips. This lower moisture content results in a higher melt temperature, most likely due to the sugar-water interaction. A likely explanation for this phenomena could be that the high energy added is propagating the growth of very small uniform crystals of sugar which result in pushing the water out of the system. These crystals have a lower total water content, even though the freezable moisture is higher, and therefore have a higher thermal stability.

Another potential mechanism of stability might be that the higher energy mixing exposes new water so binding sitse on the insoluble, non-gummy food material which comes into intimate contact with the moisture. These sites hold the moisture via capillary action, resulting in a free or freezable moisture that is then outle readily lost to the external chie environment, air or douch durino bakino.

An interesting after effect of this additional energy during processing is that the firmness of the resulting cookie decreases and elasticity increases which improves "cookie texture" sensory impressions. This might indicate that the higher work added to the chip during mixing seems to "saturate" the chips with moisture, preventing the chip from extracting moisture from the cookie crumb during baking.

It is possible to formulate and process a low fat confectionary chip by carefully controlling the ratios of primary ingredients as well as the relative energy input and time of processing. Chip processing should involve the highest possible energy of mixing which balances stickness during processing, mechanical stability during dough mixing and thermal stability in the oven. In the case of chocolary chips, the sugar to cocoa ratios should be between about 2:1 and about 4:1, and the total moisture content should be below about 15%, preferably about 11% to about 13%, to optimize melting and the mechanical character of the chips. The moisture source in the chips should preferably be a hydrated hydrocolloid system to maximize thermal stability and finished product shelf life.

These same ratios apply in the case of making a nut chip, (using peanut flour and/or a fiber in place of cocoa) and in the case of making a "white" or neutral chip by using a cereal fiber or a vegetable fiber in place of cocoa.

The low-fat confectionary chips can be candy-coated by any of the well-known procedures known to the candy art. This includes first a "soft seal" coating of an aqueous solution of suger, starch, corn syrup, color and flavor. A "hard coat" is then applied using a sugar syrup and color. A coat of smoothing syrup is then applied using a sugar syrup plus a gum, such as gum arable, and vanillin. This candy coating which can 20 vary from as little as less than 5% by weight of the chip but can be as high as 20%, is then given a final thin coating of an adble shellac, varnish, or wax at a level of less than 0.1% of the chip. Any food grade shellac or varnish can be used while a hard wax such as canapub awx is preferred if a wax is used.

The following examples are given to illustrate the scope and spirit of this invention. They are preferred embodiments, and the invention should not be limited thereto.

EXAMPLE 1

25

35

50

Aqueous Dispersion of Hydrated Food Ingredients

30 An aqueous dispersion was produced with the following composition:

Ingredients	(Weight %)
Water	79.7
Xanthan gum	1.0
Guar gum	1.0
Dextrose	2.3
Oat fiber (88.4% insoluble fiber)	3.6
Milk solids non-fat (36% protein)	12.4

The dispersion was prepared by thoroughly blending all the dry ingredients and then using a HobartTM R-200 mixer with a 20-quart (18.93 liter) bowl and a wire whip, mixing all of the ingredients for 30 seconds on 2nd speed. This pre-mix was then passed through a GaulinTM laboratory homogenizer (14M-STA) at 1500 psi (103.35 bar) 1st stage and 500 psi (34.45 bar) 2nd stage. The resulting product was a smooth aqueous dispersion with a moisture content of 81.5% and a pl of 6.7.

7

EXAMPLE 2

10

15

20

25

45

50

55

Low-Fat Chocolaty Chip

5 A chocolaty chip was prepared from the following formulation:

Ingredients	(Weight %)	
Aqueous dispersion (Ex. 1)	12.6	
Syrups	4.8	
Chocolate Flavor	1.0	
10X Sugar (50 microns)	52.4	
Low Fat Cocoa	23.0	
Non-Fat Dry Milk	4.0	
Starch	2.0	
Salt	0.2	
TOTAL	100.0	
TOTAL MOISTURE CONTENT	12.9	
TOTAL FAT CONTENT	3.5	

A wet mix of the Example 1 dispersion, syrups and chocolate flavor is first made by thoroughly mixing the wet ingredients. The 10X sugar and the remaining dry ingredients are mixed together at low speed for 8-8 minutes or until thoroughly blended. The wet mix is then added to the dry blend and blended in a mixer (Hobart) until a lumpy, caked powder is formed. The mixture is then fed into a pasta maker where it is extruded and cut into 1/8 to 1/4" (3.18 mm to 6.35 mm) short cylinders with a rotary knife. The small cylinders are then put into a rotary coating reel to round the edges. The chips are then "aged" or "tempered" overnight (for at least 12 hours to equilibrate the moisture.

The "aged" chips have an acceptable taste, texture and mouthfiel and can be used in a cookie dough mix which is baked in an oven. This dough mix typically has a moisture content of about 10-20% prior to baking and about 5-16% after baking. The chips do not melt, remain hard, and retain their integrity during the baking process. The chips, of course, can also be used in other low-fat bakery products, such as cakes. Cakes have a high moisture content, typically about 20-42% prior to baking and about 16-40% after baking. In these higher moisture, baked goods applications, the chocolate chips turn into a soft, pudding-like texture during baking which is very different than a conventional chip. The chips can also be used in low-fat non-bakery products, such as ice cream.

EXAMPLE 3

Low-Fat Chocolaty Chip

A chocolaty chip was prepared from the following formulation according to the procedure of Example 2:

Ingredients	(Weight %)	
Aqueous dispersion (Ex. 1)	14.0	
Sugar Syrup	4.8	
Chocolate Flavor	0.1	
10X Sugar (50 microns)	51.9	
Cocoa	23.0	
Non-Fat Dry Milk	4.0	
Starch	2.0	
Salt	0.2	
TOTAL	100.0	
TOTAL MOISTURE CONTENT	14.0	
TOTAL FAT CONTENT	0.7	

This chip had an improved overall chocolate taste and flavor despite the minimal amount of (0.1%) of chocolate flavor added to the formula. The fat content of this chip was less than 1% (0.7%).

EXAMPLE 4

10

15

20

25

30

50

55

Chocolaty Chip Loaf Cake

A chocolaty chip loaf cake was prepared from the following batter formulation:

Ingredients	Weight %
Aqueous Dispersion (Ex. 1)	5.4
Sugars	21.2
Flour	19.0
Liquid Egg Whites	14.6
Water	14.0
Emulsifiers	0.4
Starch	1.8
Leavening Agents	0.8
Flavors and Colors	2.1
Preservatives	0.1
Non-Fat Dry Milk	2.1
Maltodextrin	1.8
Sugar Syrup	2.1
Low-Fat Chocolaty Chips (Ex. 2)	14.6
TOTAL	100.0

The batter ingredients (excluding the chocolaty chips) were mixed in a two-stage continuous mixer. The chips were then added to the batter which was baked in bat pans. The resulting cake had excellent grain, texture and volume. The moisture content of the freshly baked cake was 38.6% by weight, the pri of the cake was 6.7, and the Aw was 0.93. The chips in the freshly baked cake had a soft fudge-like or cream consistency similar to a chocolate pudding and unlike the hard consistency of the chips in a cookie. Cookie dough has a relatively low moisture content (below about 20%) so that when the chocolaty chips of this invention are blended with cookie dough and baked, the chips do not melt, but retain their texture, shape and intentive.

EXAMPLE 5

Candy Coated Low-Fat Chocolate Chips

The chocolaty chips of Example 2 were candy coated with the following coating formulations:

Soft Seal Coating	Weight (Gms)
Dextrin	37
Boiling water	151
Sugar	48
Corn Syrup	65
Color	28
Flavor	4

Hard Coating	Weight (Gms)
Hot water	45
Sugar	65
Color	3

Smoothing Syrup	Weight (Gms)	
Gum	1	
Warm water	22	
Sugar	30	

A 3 lb. (1.38 kg) batch of the chocolate chips was placed in a pan-coating machine. The chips were first coated with the "Soft Seal" at room temperature until between a 5% to 10% coating was oblinated. Drying air at 20 archips. Then the "Hard Coating" was applied until about 1% to 5% coating was obtained. Drying air at 20 arbient temperature was blown in while applying this coating. Finally, the smoothing syrup was applied at the 1% to 5% level. The candy coating was then sealed with an edible food grade shellac applied at a level of less than 0.1%.

The candy coated chocolaty chips gave a bite similar to the texture and mouthfeel of a traditional full-fat candy-coated chocolate chip.

EXAMPLE 6

5

10

15

25

Low-Fat Pecan Flavored Chip

30 A nut chip was prepared from the following formulation following the procedure of Example 2:

Ingredients	(Weight %)
Aqueous dispersion (Ex. 1)	12.6
Sugar Syrup	4.2
Flavor (Pecan)	0.5
10X Sugar (50 microns)	58.3
Peanut Flour (32% fat)	10.5
Fiber (0% fat)	5.3
Non-Fat Dry Milk	5.8
Starch	2.1
Gum	0.2
Salt	0.5
TOTAL	100.0
TOTAL MOISTURE CONTENT	12.9
TOTAL FAT CONTENT	3.0

The pecan flavored chips had an acceptable taste, texture and mouthfeel. Similar to the Example 2 chips, they did not melt when placed in a cookie dough mix of 10-20% moisture and baked in an oven. They displayed the same pudding-like texture when placed in a cake batter containing 20-42% moisture and baked in an oven.

EXAMPLE 7

10

15

20

25

40

45

Low-Fat Pecan Flavored Chip

A nut chip was prepared from the following formulation following the procedure of Example 2:

Ingredients	(Weight %)
Aqueous dispersion (Ex. 1)	11.9
Sugar Syrup	4.2
Flavor (Pecan)	0.1
10X Sugar (50 microns)	61.4
Peanut Flour (15% fat)	19.8
Starch	2.0
Gum	0.2
Salt	0.4
TOTAL	100.0
TOTAL MOISTURE CONTENT	12.9
TOTAL FAT CONTENT	3.0

The pecan flavored chips had an acceptable taste, texture and mouthfeel. Similar to the Example 2 chips, they did not melt when placed in a cookie dough mix of 10-20% moisture and baked in an oven. They displayed the same pudding-like texture when placed in a cake batter containing 20-42% moisture and baked in an oven.

EXAMPLE 8

White Chip

A white chip was prepared from the following formulation following the procedure of Example 2:

Ingredients	(Welght %)
Aqueous dispersion (Ex. 1)	11.8
Sugar Syrup	4.0
Flavor/Color	0.4
10X Sugar (50 microns)	51.4
Fiber (0% fat)	15.0
Gum	0.2
Non-Fat Dry Milk	15.0
Starch	2.0
Salt	0.2
TOTAL	100.0
TOTAL MOISTURE CONTENT	13.0
TOTAL FAT CONTENT	0

The white (neutral flavored) chips had an acceptable taste, texture and mountheel. Similar to the Example 2 chips, they did not melt when placed in a cookied dough mix of 10-20% moisture and baked in an oven. They displayed the same pudding-like texture when placed in a cake batter containing 20-42% moisture and baked in an oven.

Those skilled in the art will make numerous modifications and variations of this invention as described herein. Consequently, only such limitations as appear in the appended claims should be placed on this invention.

Claims

15

- 1. A low-lat confectionary material containing less than 10% fat comprising a mixture of granulated sugar and insoluble, non-gummy food material at a moisture content of about 10% to about 15%, said sugar having a particle size of below 150 microns, said non-gummy food material having a fat content below about 15%, and said sugar to said non-gummy food material ratio on a weight basis between about 2:1 and about 4:1.
- A material according to claim 1, as a chocolaty chip, wherein the granulated sugar is sucrose at about 50-70%, the insoluble, non-gummy food material is cocca at about 10-30%, the sucrose having a particle size less than 60 microns, and wherein said chip contains about 3-6% of syrup, and about 3-6% non-fat dry milk solids.
- A material according to claim 2, wherein the sugar to cocoa ratio is about 3:1 and the moisture content is about 11-13%.
- 4. A material according to claim 1, as a nut chip wherein the granulated sugar is sucrose at about 50-70%, the insoluble, non-gummy food material is peanut flour or a mixture of peanut flour and a vegetable fiber at about 10-30%, the sucrose having a particle size of less than 60 microns, and wherein said chip contains about 3-6% syrup, and about 3-6% non-fat dry milk solids.
- 30 5. A material according to claim 1, as a white chip wherein the granulated sugar is sucrose at about 50-70%, the insoluble, non-gummy food material is a vegetable fiber at about 10-30%, the sucrose having a particle size of less than 60 microns, and wherein sald chip contains about 3-6% syrup, and about 3-6% non-fat dry milk solids.
- 35 6. A material according to any one of claims 1 to 5, wherein an aqueous dispersion of hydrated food material is added as a source of both free moisture and bound moisture.
 - A material according to claim 6, wherein the aqueous dispersion of hydrated food material is taken from the group consisting of hydrated polysaccharide hydrocolloids, hydrated insoluble fibers, hydrated proteins, and mixtures thereof.
 - 8. A material according to claim 7, in the form of a low-fat chocolary chip containing less than 10% cooca butter which has a doughy consistency and comprises about 50% to about 70% granulated sugar having a particle size of below 100 microns, about 10% to about 30% low-fat cooca, a moisture content of about 10 to about 15%, and an aqueous dispersion of hydrated polysaccharide hydrocolloid comprising an anionic gum and a galactomanan gum, said dispersion providing at least some of the moisture in the bound state, said sugar and cocoa being in a ratio by weight of between about 2:1 and about 4:1.
- 50 9. A material according to claim 8, wherein the granulated sugar is sucrose, the aqueous dispersion is about 6-18% of the chip and wherein the dispersion has a paste-like consistency, a Brookfield viscosity of at least 6 and comprises from 2 to 35% solids basis the weight of polysaccharide hydrocolloids, insoluble fiber and protein in the aqueous dispersion and wherein the weight ratio of polysaccharide hydrocolloid to insoluble fiber to protein is 10.8-81.1-81.
 - 10. A material according to claim 9, wherein the chip contains about 11% to about 13% moisture, about 3% to about 6% syrup, about 3% to about 6% non-fat dry milk solids, and said sugar:cocoa ratio is at about 31 on a weight basis.

- 11. A material according to any one of claims 8 to 10, wherein the chip is candy-coated and then sealed with an edible food grade shellac, varnish or wax.
- 12. A baked cookie dough containing a material according to any one of claims 8 to 11, wherein the moisture content of the baked dough is about 5-18% and said chip is in a form which retains its integrity and has not melted.
 - 13. A baked loaf cake containing material according to any one of claims 8 to 11, wherein the moisture content of the baked cake is about 16-40% and said chips have a melted, pudding-like consistency.
- 14. A baked loaf cake according to claim 13, wherein the moisture content of the cake is about 38.6%, the pH about 6.7 and the Aw about 0.89.
- 15. A process for making a fat-free chocolaty material containing less than about 10% cocoa butter which

mixing into a dough about 50% to about 70% granulated sugar, about 10% to about 30% low-fat cocoa, and about 10% to about 15% moisture, said sugar having a particle size below 100 microns, and said sugar to cocoa ratio being between about 2:1 and about 4:1;

forming the dough into a suitable shape; and

cutting the shape into pieces.

- 16. A process according to claim 15, wherein an aqueous dispersion of hydrated food material is added to the dough mixture as a source of moisture.
- 25 17. A process according to claim 16, wherein the aqueous dispersion of hydrated food material is taken from the group consisting of hydrated polysaccharide hydrocolloids, hydrated insoluble fibers, hydrated proteins, and mixtures thereof.
 - A process according to any one of claims 15 to 17, wherein the dough contains about 3-6% of a syrup, and about 3-6% non-fat dry milk solids.
 - 19. A process according to any one of claims 15 to 18, wherein the granulated sugar in the dough is sucrose having a particle size of less than about 60 microns, the sugar to cocoa ratio is about 3:1 and moisture content of the dough is about 11-13%.
 - A process according to claim 19, wherein the granulated sucrose in the dough is at least 80% of the total sugar.
 - 21. A process according to any one of claims 15 to 20, wherein the chocolaty chips are added to a cookie dough containing about 10-20% moisture, and the dough is baked, said chips in the baked cookie dough not melting, or losing their integrity.
- 22. A process according to any one of claims 15 to 20, wherein the chips are added to a loaf cake batter containing 20-42% moisture, and the loaf cake is baked, said chips in the freshly baked loaf cake having a melted, pudding-like consistency.
 - 23. A process according to claim 22, wherein the freshly baked loaf cake has a moisture content of about 38.6%, a pH of about 6.7 and an Aw of about 0.89.

55

50

10

20

35



(1) Publication number:

0 564 077 A3

© EUROPEAN PATENT APPLICATION

(P) Application number: 93300874.0

(i) Int. Cl.⁵: **A23G** 1/00, A23G 3/02, A23G 1/04

2 Date of filing: 05.02.93

Priority: 20.02.92 US 839525

Date of publication of application: 06.10.93 Bulletin 93/40

Designated Contracting States:
 AT BE CH DE DK ES FR GB GR IE IT LI LU MC
 NL PT SE

Date of deferred publication of the search report: 17.08.94 Bulletin 94/33 Applicant: KRAFT GENERAL FOODS, INC. 250 North Street
 White Plains New York 10625 (US)

(ventor: Fitch, Mark David 7 Maple Avenue Stonybrook, New York 11780 (US) Inventor: Anderson, Wendy Ann 347 West End Avenue No.2A New York, New York 10024 (US) Inventor: Eckhardt, Gerard 413 Lindan Street

Beilmore, New York 11710 (US) Inventor: Anelich, Mario Anthony 63 Merritt Avenue

Dumont, New Jersey 07628 (US) Inventor: Frake, Barry Nell 1 Guil Cove Northport, New York (US)

Northport, New York (US) Inventor: Lang, Kevin Walter 1 Tulip Drive Lloyd Neck, New York 11743 (US)

Representative: Eyles, Christopher Thomas W.P. THOMPSON & CO. Celcon House

289-293 High Holborn London WC1V 7HU (GB)

Solution Low-fat confectionary material and process for making same.

② Fat in a contectionary chip is reduced to below about 10% by using a low-fat insoluble, non-gummy food material and small particle sugar (less than 100 microns) in combination with about 13% moisture. The sugar to non-gummy food material ratio must be between 2:1 and 4:1 and the moisture between about 10% to about 15%. Hot/ated food ingredients are added to retain at least some of the moisture in the bound state. Other ingredents which may be added to the formulation include syrups, milk solids and starch. The chips can be made by simply blending the dry ingredients and adding the moisture to start the start of the

form a dough in the form of a dry, crumbly paste. The dough is mixed or worked up well and then formed into the desired shape. The shape is then cut into pieces similar to chocolate chips.

EP 0 564 077 A3

EUROPEAN SEARCH REPORT

Application Number EP 93 30 0874

	DOCUMENTS CONSIDER	ED TO BE RELEVAN	Т	
Category	Citation of document with indication of relevant passages	a, where appropriate,	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CL5)
X	FR-A-2 384 461 (GERD SA 1978 * the whole document *	MMET) 20 October	1-3	A23G1/00 A23G3/02 A23G1/04
x	EP-A-0 276 353 (H. BAHL	- CENS KERSEMBOIR) 3	1	
^	August 1988 * page 2, line 1 - line 1-5,8,11,12 *		•	i
P, X	WO-A-92 08367 (J. R. AN * the whole document *	DRE) 29 May 1992	1-3	
A	EP-A-0 052 919 (AMSTAR	CORP.) 2 June 1982		
^	GB-A-2 031 705 (A. H. R April 1980 * the whole document *	OBINS COMP.) 30	1	
д,х	EP-A-0 340 035 (KRAFT I November 1989 * page 5, line 25 - pag * page 21, line 54 - pa * page 23, line 30 - pa examples 42-47 * * page 25, line 10 - li 1-3,15,35,38 *	e 9, line 29 * ge 22, line 16 * ge 24, line 35;	1,6,7	TECHNICAL FIELDS SEARCHED (In.C.S) A23G
A	US-A-4 504 513 (D. J. B	LACK) 12 March 1985 -		
٨	EP-A-0 437 360 (WARNER 1991	LAMBERT) 17 July		
٨	WO-A-91 09537 (THE PROC 11 July 1991 * abstract *	TER & GAMBLE COMP.)	1	
i		-/		
i	The present search report has been dra	wa up for all claims		
	Place of search	Date of completion of the search	<u> </u>	Exercises
	THE HAGUE	16 June 1994	Guy	on, R
X : par Y : par doc A : tecl	CATEGORY OF CITED DOCUMENTS iticisarly relevant if taken alone iticisarly relevant if combined with another unsent of the same category inclogical background -written disclosure	T: theory or princip E: earlier patent do after the filling d D: document cited f L: document cited f d: member of the s	or other reasons	



EUROPEAN SEARCH REPORT

Application Number EP 93 30 0874

DOCUMENTS CONSIDERED TO BE RELEVANT					
Category	Citation of document with i	sdication, where appropriate, scages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CL5)	
A	WO-A-80 01868 (VITA 1980 *abstract * * page 1, line 1 - * page 7, line 32 -	MINS INC.) 18 September page 4, line 23 * page 10, line 19 *	1,11,15		
A	WO-A-88 09127 (FERM December 1988 * the whole documen		1		
				TECHNICAL FEELDS SEARCHED (Int.Cl.5)	
	The present search report has b	ees draws up for all claims Due of completes or the users		Danie	
THE HAGUE CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if comblete ditth another document of the same category A: technological background Of the comblete document F: intermediate document		L : document cited t	16 June 1994 Guyon, R T: theory or principle underlying the investice E: section principle underlying the investice E: section principle underlying the investice D: document cited in the application L: document cited for other reason A: masker of the same patent family, corresponding		